



Ecodesign EU Declaration of Conformity

DoC Scan-Line 900 2408-2019 **Product fiche**



Manufacturer	Heta A/S
Adress	Jupitervej 22, DK 7620 Lemvig
E-mail	heta@heta.dk
Website	www.heta.dk
Telephone	+45 9663 0600

Model identifier | Scan-Line 900 Side windows, 900B Side windows, 900S Side windows Series

The identified product described above is in conformity with:		
The relevant EU harmonized regulations:		
DIR 2009/125/EF		
REG (EU) 2015/1185		
REG (EU) 2015/1186		
REG (EU) 2017/1369		
REG (EU) 305/2011		
The relevant harmonized standards		
EN 13240:2001/A2:2004		
CEN/TS 15883:2010		

Characteristics when operating with the preferred fuel only				
Heat output				
Item	Symbol	Value/Unit		
Nominal heat output	P _{nom}	6,6 kW		
Minimum heat output	P _{min}			
Useful efficiency (NCV as received)				
Useful efficiency at nominal heat output	$\eta_{\scriptscriptstyle ext{th, nom}}$	82%		
Useful efficiency at minimum heat output	$oldsymbol{\eta}_{ ext{th, min}}$			
Auxiliary electricity consumption				
At nominal heat output	el _{max}	- kW		
At minimum heat output	el _{min}	- kW		
In standby mode	el _{SB}	- kW		

Type of heat output/room temperature control		
Yes		
No		

Other control options	
room temperature control, with presence detection	No
room temperature control, with open window detection	No
with distance control option	No

Notified body relevant to the assessment and verification of
constancy of performance

Danish Technological Institute, DK-8000 Aarhus No. 1235. Report no. 300-ELAB-2408-EN

Fuel	Preferred fuel	Other suit- able fuel
Wood logs with moisture content ≤ 25 %	Yes	No
Compressed wood with moisture content < 12 %	No	No
Other woody biomass	No	No
Non-woody biomass	No	No
Anthracite and dry steam coal	No	No
Hard coke	No	No
Low temperature coke	No	No
Bituminous coal	No	No
Lignite briquettes	No	No
Peat briquettes	No	No
Blended fossil fuel briquettes	No	No
Blended biomass and fossil fuel briquettes	No	No
Other blend of biomass and solid fuel	No	No

Emissions at		mg/Nm³ (13 % O ₂)			
nominal heat output	η _s %	PM	OGC	СО	NO _x
output	≥ 65	≤ 40	≤ 120	≤ 1500	≤ 200
	72	9	113	1244	76

Technical documentation	
Indirect heating functionality:	No
Direct heat output:	6,6 kW
Energy Efficiency Index (EEI):	EEI 109
Fluegas temperature at nominal heat output	T 265°C
Energy efficiency class	A^{+}

Safty	
Reaction to fire	A1
Test of fire safety in connection with the burning of wood	Approved
Distance to combustible materials Rear. Without insulation / with insulation Sides distance to combustible materials Furniture distance	Minimum distances in mm 125/150 400 900

Signed on behalf the manufacturer of 07.02.2022



Γhe chimney sweep's signature	Date

Ο:		
SIC	ınatı	ıre