

Declaration of performance according to regulation(EU) 305/2011

DoP 01-25-CPR305211

No.	Information according to (EU) 305/2011	Registration by the manufacturer
1	Unique identification code of the product type	Bullerjan B4
2	Intended use(s)	Space heating in residential buildings
3	Manufacturer / trade mark	Bullerjan GmbH Neuwarmbüchener Straße 2, 30916 Isernhagen-Kirchhorst GERMANY
	E-Mail	info@bullerjan.com
4	Authorised representative	Bullerjan GmbH Neuwarmbüchener Straße 2, 30916 Isernhagen-Kirchhorst GERMANY
	E-Mail	info@bullerjan.com
5	System(s) of assessment and verification of constancy of performance of the construction product	System 3
6	The notified test laboratory has performed the initial test according to system 3. Notified body(ies)	NB-1625 Rhein-Ruhr Feuerstätten Prüfstelle GmbH Im Lipperfeld 34b, 46047 Oberhausen, DEUTSCHLAND Test report number RRF – 1021 25 1204
7	Harmonised technical specifications	EN 16510-2-1:2022
8	Essential characteristics	
	Mechanical resistance and stability	
	Load bearing capacity	0 kg
	Safety in case of fire	
	Protection of combustible materials	Minimum distance to combustible materials – bottom db = 20 mm Minimum distance to combustible materials – floor in front dF = 400 mm Minimum distance to combustible materials – ceiling dc = 750 mm Minimum distance to combustible materials – rear dR = 300 mm Minimum distance to combustible materials – side ds = 200 mm Minimum distance to combustible materials – side radiation area dL = 500 mm Minimum distance to adjacent combustible materials – front radiation area dP = 1200 mm Material type and thickness of the protective insulation mater s = 0 mm
	Hygiene, health and environment	
	<i>Emissions at nominal heat output</i>	
	Carbon monoxide (CO)	1400 mg/m³
	Nitrogen oxides (NOx)	150 mg/m³
	Organic gaseous carbon (OGC)	80 mg/m³
	Particulate matter (PM)	35 mg/m³
	<i>Emissions at part load heat output</i>	
	Carbon monoxide (CO)	NPD mg/m³
	Nitrogen oxides (NOx)	NPD mg/m³
	Organic gaseous carbon (OGC)	NPD mg/m³
	Particulate matter (PM)	NPD mg/m³

No.	Information according to (EU) 305/2011	Registration by the manufacturer
	Safety and accessibility in use	
	<i>Data for installation to a chimney at nominal heat output</i>	
	Flue gas outlet temperature	308 °C
	Minimum flue draught	12 Pa
	Flue gas mass flow	8,0 g/s
	<i>Data for installation to a chimney at part load heat output</i>	
	Flue gas outlet temperature	NPD °C
	Minimum flue draught	NPD Pa
	Flue gas mass flow	NPD g/s
	<i>Data for installation to a chimney regarding fire safety on safety test heat output</i>	
	Fire safety of installation to the chimney	T400 - G
	Energy economy and heat retention	
	<i>Appliance's thermal output and energy efficiency at nominal heat output</i>	
	Space heat output	10,0 kW
	Water heat output	NPD kW
	Efficiency	82 %
	<i>Appliance's thermal output and energy efficiency at part load heat output</i>	
	Space heat output	NPD kW
	Water heat output	NPD kW
	Efficiency	NPD %
	<i>Space heating efficiency</i>	
	Seasonal space heating efficiency at nominal heat output	65 %
	Energy Efficiency	Energy Efficiency Index (EEI) 109
		Energy efficiency class A+
	Electric power consumption at nominal heat output	NPD kW
	Electric power consumption at part load heat output	NPD kW
	Power consumption in standby mode	NPD kW
	Sustainable use of natural resources	
	Environmental sustainability	NPD
9	The performance of the product identified above is in conformity with the set of declared performance. This declaration of performance is issued, in accordance with regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.	

Signed on behalf of the manufacturer

Name Kevin Senff

Place and Date Isernhagen, 09.11.2025

Signature 

[illegible]

[illegible]
