Declaration of performance according to regulation(EU) 305/2011

DoP 01-25-CPR305211

Bullerjan®

No.	Information according to (EU) 305/2011	Registration by the manufacturer
1	Unique identification code of the product type	Bullerjan B4
2	Intended use(s)	Space heating in residential buildings
3	Manufacturer / trade mark	Bullerjan GmbH Neuwarmbüchener Straße 2, 30916 Isernhagen-Kirchhorst GERMANY
	E-Mail	info@bullerjan.com
4	Authorised representative	Bullerjan GmbH Neuwarmbüchener Straße 2, 30916 Isernhagen-Kirchhorst GERMANY
	E-Mail	info@bullerjan.com
5	System(s) of assessment and verification of constancy of performance of the construction product	System 3
6	The notified test laboratory has performed the initial test according to system 3. Notified body(ies)	NB-1625 Rhein-Ruhr Feuerstätten Prüfstelle GmbH Im Lipperfeld 34b, 46047 Oberhausen, DEUTSCHLAND Test report number RRF-40 18 4884-1
7	Harmonised technical specifications	EN 16510-2-1:2022
8	**Essential characteristics**	
	Mechanical resistance and stability	**Art: Typ BE, Typ CA**
	Load bearing capacity	0 kg
	Safety in case of fire	
	Protection of combustible materials	Minimum distance to combustible materials – bottom d_B = 20 mm
		Minimum distance to combustible materials – floor in front d_F = 400 mm
		Minimum distance to combustible materials – ceiling d_C = 750 mm
		Minimum distance to combustible materials – rear d_R = 300 mm
		Minimum distance to combustible materials – side d_S = 200 mm
		Minimum distance to combustible materials – side radiation area d_L = 500 mm
		Minimum distance to adjacent combustible materials – front radiation area d_P = 1200 mm
		Material type and thickness of the protective insulation mater s = 0 mm
	Hygiene, health and environment	
	Emissions at nominal heat output	
	Carbon monoxide (CO)	875 mg/m³
	Nitrogen oxides (NO_x)	140 mg/m³
	Organic gaseous carbon (OGC)	80 mg/m³
	Particulate matter (PM)	35 mg/m³
	Emissions at part load heat output	
	Carbon monoxide (CO)	NPD mg/m³
	Nitrogen oxides (NO_x)	NPD mg/m³
	Organic gaseous carbon (OGC)	NPD mg/m³
	Particulate matter (PM)	NPD mg/m³

No.	Information according to (EU) 305/2011	Registration by the manufacturer	
	Safety and accessibility in use		
	Data for installation to a chimney at nominal heat output		
	Flue gas outlet temperature	300 °C	
	Minimum flue draught	12 Pa	
	Flue gas mass flow	7,1 g/s	
	Data for installation to a chimney at part load heat output		
	Flue gas outlet temperature	NPD °C	
	Minimum flue draught	NPD Pa	
	Flue gas mass flow	NPD g/s	
	Data for installation to a chimney regarding fire safety on safety test heat output		
	Fire safety of installation to the chimney	T400 - G	
	Energy economy and heat retention		
	Appliance's thermal output and energy efficiency at nominal heat output		
	Space heat output	8,0 kW	
	Water heat output	NPD kW	
	Efficiency	82 %	
	Appliance's thermal output and energy efficiency at part load heat output		
	Space heat output	NPD kW	
	Water heat output	NPD kW	
	Efficiency	NPD %	
	Space heating efficiency		
	Seasonal space heating efficiency at nominal heat output	65 %	
	Energy Efficiency	Energy Efficiency Index (EEI)	109
		Energy efficiency class	A+
	Electric power consumption at nominal heat output	NPD kW	
	Electric power consumption at part load heat output	NPD kW	
	Power consumption in standby mode	NPD kW	
	Sustainable use of natural resources		
	Environmental sustainability	NPD	
9	The performance of the product identified above is in conform ity with the set of declared performance. This declaration of performance is issued, in accordance with regulation (EU) No 305/2011, under the sole respon of the manufacturer identified above.		

Signed on behalf of the manufacturer

Name Kevin Senff

Place and Date Isernhagen, 09.11.2025

Signature

rial

ısibility