

**Declaration of performance in accordance with
Regulation (EU) No 305/2011**

DoP 01-25-CPR305211

No.	Information in accordance with Regulation (EU) No 305/2011	Registration by the manufacturer
1	Unique identification code of the product type	Bullerjan Free Flow FF18 - Type 04
2	Intended use(s)	Space heating in residential buildings
3	Brand / Manufacturer	Bullerjan GmbH Neuwarmbüchener Straße 2, 30916 Isernhagen-Kirchhorst GERMANY
	Email	info@bullerjan.com
4	Authorised representative	Bullerjan GmbH Neuwarmbüchener Straße 2, 30916 Isernhagen-Kirchhorst GERMANY
	Email	info@bullerjan.com
5	System(s) for assessing and verifying the constancy of performance of the construction product	System 3
6	The notified testing laboratory carried out the initial inspection in accordance with System 3. Notified body(ies).	NB-1625 Rhein-Ruhr Feuerstätten Prüfstelle GmbH Im Lipperfeld 34b, 46047 Oberhausen, GERMANY Test report number RRF – 40 19 5236
7	Harmonised technical specifications	EN 16510-2-1:2022
8	Key features	Type of fireplace: Type B
	Mechanical strength and stability	
	Load-bearing capacity	0 kg
	Fire safety	Not approved for multiple occupancy
	Protection of combustible materials	Minimum distance from combustible materials – Distance below the fireplace d _B = 0 mm Minimum distance from combustible materials – Distance to the front at floor level d _F = 0 mm Minimum distance from combustible materials – Distance to the ceiling d _C = 750 mm Minimum distance from combustible materials – Distance to rear wall d _R = 750 mm Minimum distance from combustible materials – Distance to side wall d _S = 650 mm Minimum distance from combustible materials – Distance to side wall in the radiation zone d _L = 0 mm Minimum distance from adjacent combustible materials – Distance within the radiation zone of the viewing window d _P = 1400 mm Type and thickness of the thermal insulation s = 0 mm
	Hygiene, health and environmental protection	
	<i>Emissions at rated heat output</i>	
	Carbon monoxide (CO)	1300 mg/m³
	Nitrogen (NO _x)	130 mg/m³

	Organic gaseous carbon (OGC)	120	mg/m³
	Particulate matter (PM)	35	mg/m³
	Emissions at partial load heat output		
	Carbon monoxide (CO)	NPD	mg/m³
	Nitrogen (NOx)	NPD	mg/m³
	Organic gaseous carbon (OGC)	NPD	mg/m³
	Particulate matter (PM)	NPD	mg/m³
No.	Information in accordance with Regulation (EU) No 305/2011	Entry by the manufacturer	
	Safety and accessibility during use		
	Data for installation on a chimney at nominal heat output		
	Temperature at the flue outlet	229	°C
	Minimum delivery pressure	12	Pa
	Exhaust gas mass flow	21.5	g/s
	Data for installation on a chimney at partial load heat output		
	Temperature at the exhaust manifold	NPD	°C
	Minimum delivery pressure	NPD	Pa
	Exhaust gas mass flow	NPD	g/s
	Data regarding installation on a chimney with regard to fire safety		
	Fire safety for installation on a chimney	T400 - G	
	Energy saving and thermal insulation		
	Heat output and energy efficiency of the appliance at rated heat output		
	Room heat output	30.0	kW
	Water heat output	NPD	kW
	Efficiency	87	%
	Heat output and energy efficiency of the unit at partial load heat output		
	Room heat output	NPD	kW
	Water heat output	NPD	kW
	Efficiency	NPD	%
	Space heating efficiency		
	Annual space heating efficiency at rated heat output	65	%
	Energy efficiency	Energy Efficiency Index (EEI)	116
		Energy efficiency class	A+
	Power consumption at rated heat output	NPD	kW
	Power consumption at partial load heating output	NPD	kW
	Power consumption in standby mode	NPD	kW
	Sustainable use of natural resources		
	Environmental sustainability	NPD	
9	The performance of the above product complies with the declared performance(s). The manufacturer named above is solely responsible for drawing up the declaration of performance in accordance with Regulation (EU) No 305/2011.		

Signed on behalf of the manufacturer

Isernhagen

Name _____

Place and date 09/11/2025 _____

Signature _____

