DECLARATION OF PERFORMANCE

as per Regulation (EC) 305/2011

AUSTROFLAMM

Sina Xtra

1. LEK no.	KO 0062
2. Model	Stove
3. Intended use	Space heating in residential buildings
4. Manufacturer	Austroflamm GmbH Austroflamm-Platz 1 A-4631 Krenglbach
5. Representative	-
6. System(s) for assessing and verifying the constancy of performance of the construction product	3

Test laboratory identification number/test report number	1880 / 1880-CPR-091TR-2/1880-CPR-044TR-22
Harmonized technical specification	EN 16510-2-1:2022
Load bearing capacity (kg)	70
Minimum distance to combustible materials – bottom dB [mm]	0
Minimum distance to combustible materials – floor in front dF [mm]	1230
Minimum distance to combustible materials – distance to ceiling dC [mm]	750
Minimum distance to combustible materials - distance to rear dR [mm]	150
Minimum distance to combustible materials – left side dS_1 [mm]	50
Minimum distance to combustible materials – right side dS_2 [mm]	50
Minimum distance to combustible materials – left side radiation area dL_1 [mm]	920
Minimum distance to combustible materials – right side radiation area dL_2 [mm]	920
Minimum distance to adjacent combustible materials (e.g. furniture) dP [mm]	1000
Material type and material thickness of the thermal insulation	-
CO at 13% O2 at nominal heat output [mg/Nm³]	539
NOX at 13% O2 at nominal heat output [mg/Nm³]	95
OGC at 13% O2 at nominal heat output [mg/Nm³]	21
Particulate matter (PM) at 13% O2 at nominal heat output [mg/Nm³]	20
CO at 13% O2 at part load heat output [mg/Nm³]	-
NOX at 13% O2 at part load heat output [mg/Nm³]	-
OGC at 13% O2 at part load heat output [mg/Nm³]	-
Particulate matter (PM) at 13% O2 at part load heat output [mg/Nm³]	-
Flue gas temperature at the nozzle at nominal heat output [°C]	271
Minimum delivery pressure at nominal heat output [Pa]	12
Flue gas mass flow at nominal heat output [g/s]	4.4
Flue gas temperature at part load heat output [°C]	-

DECLARATION OF PERFORMANCE

as per Regulation (EC) 305/2011

Sina Xtra

1. LEK no.	KO 0062
2. Model	Stove
3. Intended use	Space heating in residential buildings
4. Manufacturer	Austroflamm GmbH Austroflamm-Platz 1 A-4631 Krenglbach
5. Representative	-
6. System(s) for assessing and verifying the constancy of performance of the construction product	3

Minimum flue draught at part load heat output [Pa]	-
Flue gas mass flow at part load heat output [g/s]	-
Fire safety for installation to the chimney	T400 G
Nominal room heat output [kW]	6.0
Nominal water heat output [kW]	-
Efficiency at nominal heat output [%]	86.3
Partial load room heat output [kW]	-/-
Partial load water heat output [kW]	-/-
Efficiency at at part load heat output [%]	-
Space heating annual use efficiency [%]	76.3
Energy efficiency index (EEI)	115
Energy efficiency class	A+
Auxiliary power consumption at nominal heat output [kW]	-
Auxiliary power consumption at minimum heat output [kW]	-
Auxiliary power consumption in standby condition [kW]	-
Environmental sustainability	NPD

The performance of the aforementioned product corresponds to the declared performance(s). The above-mentioned manufacturer is solely responsible for the preparation of this declaration of performance in accordance with Regulation (EU) No. 305/2011.

Krenglbach, 14/10/2025

Andreas Schönfeld
Managing Director